

**SS10 Explosion Proof PTZ Camera****Certificate**

Certificate Mark	Exd II C T6 Gb/Ext D A21 IP65 T80°C
Certificate No	CNEx14.3487X
Standards	Q/320412 ZAF007-2014

Mechanical

Housing	Stainless steel 304 or 316L
IP	IP65
Cable thread hole	1pcs G3/4 or NPT3/4
Wiper	yes

Electrical

Voltage	AC85V AC265V or DC24V or AC24V
Power	35W /55W (with thermostat)

Ambient

Ambient temperature	-25 to +60°C
Air pressure	80Kpa to 106Kpa
Relative Humidity	≤95% (no condensation)

Communication

Communication	support analog video output
485 Communication	Support Pelco-D, Pelco-P
Communicate Rate	2400 to 19200bps

Pan & Tilt

Horizontal	360°
Horizontal speed	0.1-45°/s
Vertical	-90 to +90°

Camera

Image Sensor	1/3" interline-transfer CCD
Effective pixel	PAL 976*582 NTSC 976*494
Min. Illumination	Color 0.04Lux B/W: 0.004Lux
Shutter Time	1/50(1/60) sec~ 1/10,000 sec
Horizontal resolution	700TVL (color), 720TVL (B&W)
S/N ratio	50dB AGC off

Lens

Focal Length	4-92mm, 23X/or 36X optical
Aperture Range	F1.5-F3.6
Angle of View	49-2.2 degree(Wide-Tele)

Min. Working Distance	10mm-1500mm(Wide-Tele)
Zoom Speed	Approx. 3s(Optical, Wide-Tele)

Control

Camera address	on/off 0-254
Focus Mode	Auto/Manual/One touch
Gain	off/ lower/ higher
Slow shutter	X256 MAX
White Balance	Auto /Indoor/Outdoor/Manual/auto tracking
Video	3D DNR, mirror, brightness, Contrast, Sharpness adjustab
Digital zoom	X16
Zoom display	on/off
ZCF control mode	mode 1, mode 2
RS485	protocol, baud rate, address

General

Cable	integrated cable
Size	310*305*381mm
Weight	17kg
Mounted	wall, pole
Wall bracket	SP20

Dimension

